INTEGRA VIVID




The Integra Vivid is a 7" high-resolution HMI color touchscreen display. The Vivid is used to visualize print jobs and statuses of certain Markoprint printers that do not have a built-in display. With the help of the Integra Vivid, at a glance you can see whether the printing system is active as well as check the print speed & cartridge ink levels. You can also start & stop, delay, change intensity, set passwords, and adjust encoder signals right from the HMI.

With its IP52 protection class, it is protected in dusty production environments and against dripping water.









Scan for more info



visit » www.automatedmarking.com





Dayfayyan ay data	
Performance data	
Supported print systems	X1JET systems, integra PP 108 and integra PP RAZR
Supported print technologies	HP, LX, MX, XR, PP
Max. number of print heads	1
Max. number of production lines	1
Weight system	1275 g
Weight holder	500 g
Display size	7" (17,8 cm)
Depth	27,3 mm
Width	200,6 mm
Height	132,2 mm (without holder and connections)
Text design	over idesign8+ Software
Parameter input	over idesign8+ Software as well as at the integra Vivid
User language	German, English
Protection class	IP52
Temperature range	5 to 40°C
Relative humidity, max.	10 to 90% (non-condensing)
Max. operating time	The device is designed for continuous operating

Technical changes reserved at any time



ADVANTAGES

- » 7" touchscreen
- » Messages are created with the included Software

200 Business Park Drive - Suite 310, Armonk, NY 10504

Telephone: 914-495-3807 | 1-800-345-6667

Web: www.automatedmarking.com | Email: info@automatedmarking.com

